

Amendments to the Claims

This following listing of claims will replace all prior versions and listing of claims in the application.

Listing of claims.

1-12 (*Withdrawn*)

13. (*Currently Amended*) A non-aqueous petroleum spray distillate product comprising a petroleum distillate and a shear-thinning thixotropic thickener, wherein the thickener comprises:

- a. from about 2 percent to about 30 percent of a triblock copolymer; and
- b. from about 70 percent to about 98 percent of a hydrocarbon oil.

14. (*Canceled*)

15. (*Previously Presented*) A product set forth in claim 14, wherein said thixotropic thickener is present in an amount of from about 0.2 to about 12 percent by weight of the composition.

16. (*Previously Presented*) A product as set forth in claim 15, wherein said petroleum distillate is selected from the group consisting of mineral oils, mineral spirits, naphthalene, and vegetable oils.

17. (*Previously Presented*) A product set forth in claim 16, wherein said petroleum distillate is a mineral oil.

18. (*Previously Presented*) A product as set forth in claim 16, selected from the group consisting of furniture oils; furniture polishes and cleaners; baby oils; sunscreens; nail enamel dryers; hair oils; bath, body and massage oils; makeup removers; gasoline additives; fuel injection cleaners; carburetor cleaners; cleaning solvents; water repellents; and general household oil.

19. ***(Previously Presented)*** A product as set forth in claim 18, comprising a furniture oil wherein said petroleum distillate is a mineral oil, and said thixotropic thickener comprises from about 2 percent to about 30 percent of a triblock copolymer and from about 70 percent to about 98 percent of a hydrocarbon oil.

20. ***(Previously Presented)*** A product as set forth in claim 19, wherein said thickener comprises from about 0.2 to about 9 percent by weight of the product.

21. ***(New)*** A non-aqueous petroleum distillate product comprising:

- a) a petroleum distillate having a viscosity of less than about 130 SUS at 100° F.;
and
- b) a sheer-thinning thixotropic thickener that enables the product to form a mist when dispensed by a spray mechanism, wherein the thixotropic thickener consists essentially of a triblock copolymer and a hydrocarbon oil.

22. ***(New)*** A product as set forth in claim 21, wherein the triblock copolymer and the hydrocarbon oil are present in a ratio of between 1:50 and 1:2.